



**Order specification DA series Mercury Pressure Transducer with mV/V output**

Order specification	DA																			
<b>Standard configuration</b>																				
<input type="checkbox"/> <b>Total measurement error FSO</b>	DA																			
<input type="checkbox"/> 0.25%		1																		
<input type="checkbox"/> 0.50%		2																		
<b>Output signal</b>																				
<input type="checkbox"/> 2,0 mV/V			0 0																	
<input type="checkbox"/> 3,3 mV/V			5 0																	
<b>Thread connection</b>																				
<input type="checkbox"/> 1/2" UNF 2A				1 2 A																
<input type="checkbox"/> M18 x 1,5 A				1 8 A																
<input type="checkbox"/> M18 x 1,5 B				1 8 B																
<b>Pressure range [psi]</b>																				
<input type="checkbox"/> 250	*					P 2 5 Z														
<input type="checkbox"/> 500	*					P 5 0 Z														
<input type="checkbox"/> 750	*					P 7 5 Z														
<input type="checkbox"/> 1500						P 1 5 H														
<input type="checkbox"/> 3000						P 3 0 H														
<input type="checkbox"/> 5000						P 5 0 H														
<input type="checkbox"/> 6000						P 6 0 H														
<input type="checkbox"/> 7500						P 7 5 H														
<input type="checkbox"/> 9000						P 9 0 H														
<input type="checkbox"/> 10000						P 1 0 T														
<input type="checkbox"/> 12000						P 1 2 T														
<input type="checkbox"/> 15000						P 1 5 T														
<input type="checkbox"/> 20000						P 2 0 T														
<input type="checkbox"/> 30000						P 3 0 T														
<b>Shaft length (rigid)</b>																				
<input type="checkbox"/> 152 mm, 6" (Standard)						S 0														
<input type="checkbox"/> 203 mm, 8,0"						S 1														
<input type="checkbox"/> 254 mm, 10,0"						S 2														
<input type="checkbox"/> 318 mm, 12,5"						S 3														
<input type="checkbox"/> 356 mm, 14,0"						S 4														
<input type="checkbox"/> 457 mm, 18,0"						S 5														
<input type="checkbox"/> Special shaft length						S 9														
<b>Length of flexible capillary</b>																				
<input type="checkbox"/> No flexible capillary						F 0														
<input type="checkbox"/> 457 mm, 18" (standard)						F 5														
<input type="checkbox"/> 610 mm, 24"						F 6														
<input type="checkbox"/> 760 mm, 30"						F 8														
<input type="checkbox"/> Special length						F 9														
<b>Diaphragm</b>																				
<input type="checkbox"/> 17-4 PH	**																			
<input type="checkbox"/> Alloy C4	**																			
<input type="checkbox"/> Alloy 718	**																			
<input type="checkbox"/> Special diaphragm																				
<b>Sensor medium</b>																				
<input type="checkbox"/> Mercury "M" Group																				
<b>Electrical connection</b>																				
<input type="checkbox"/> 6-pole connection (standard)																				6 P
<input type="checkbox"/> 8-pin connection																				8 P
<b>Special design</b>																				
<input type="checkbox"/> No special design																				0 0 0
<input type="checkbox"/> Special design																				x x x

\* Only available with M18 thread connection.  
 \*\* As a standard, all diaphragms are coated against adhesive and glutinous media. Special coatings are available on request.  
 \*\*\* For cable exit, please confirm cable length. Unless specified, the standard length will be 3 m.

