

Use this form to generate your exact part number. Then telephone (847) 981-0003 or fax (847) 981-9333 for price and delivery.



Order specification DA series NTX Non-Mercury

Order specification	DA	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Standard configuration																			
<input type="checkbox"/> Total measurement error FSO	DA																		
<input type="checkbox"/> 0.25%		1																	
<input type="checkbox"/> 0.50%		2																	
Output signal																			
<input type="checkbox"/> 2,0 mV/V		0 0																	
<input type="checkbox"/> 3,3 mV/V		5 0																	
Thread connection																			
<input type="checkbox"/> 1/2" UNF 2A				1 2 A															
<input type="checkbox"/> M18 x 1,5 A				1 8 A															
<input type="checkbox"/> M18 x 1,5 B				1 8 B															
Pressure range [psi]																			
<input type="checkbox"/> 250		*			P 2 5 Z														
<input type="checkbox"/> 500		*			P 5 0 Z														
<input type="checkbox"/> 750		*			P 7 5 Z														
<input type="checkbox"/> 1500					P 1 5 H														
<input type="checkbox"/> 3000					P 3 0 H														
<input type="checkbox"/> 5000					P 5 0 H														
<input type="checkbox"/> 6000					P 6 0 H														
<input type="checkbox"/> 7500					P 7 5 H														
<input type="checkbox"/> 9000					P 9 0 H														
<input type="checkbox"/> 10000					P 1 0 T														
<input type="checkbox"/> 12000					P 1 2 T														
<input type="checkbox"/> 15000					P 1 5 T														
<input type="checkbox"/> 20000					P 2 0 T														
<input type="checkbox"/> 30000					P 3 0 T														
Shaft length (rigid)																			
<input type="checkbox"/> 152 mm, 6" (Standard)						S 0													
<input type="checkbox"/> 203 mm, 8,0"						S 1													
<input type="checkbox"/> 254 mm, 10,0"						S 2													
<input type="checkbox"/> 318 mm, 12,5"						S 3													
<input type="checkbox"/> 356 mm, 14,0"						S 4													
<input type="checkbox"/> 457 mm, 18,0"						S 5													
<input type="checkbox"/> Special shaft length						S 9													
Length of flexible capillary																			
<input type="checkbox"/> No flexible capillary						F 0													
<input type="checkbox"/> 457 mm, 18" (standard)						F 5													
<input type="checkbox"/> 610 mm, 24"						F 6													
<input type="checkbox"/> 760 mm, 30"						F 8													
<input type="checkbox"/> Special length						F 9													
Diaphragm																			
<input type="checkbox"/> 17-4 PH		**								R									
<input type="checkbox"/> Alloy C4		**								H									
<input type="checkbox"/> Alloy 718		**								I									
<input type="checkbox"/> Special diaphragm										S									
Sensor medium																			
<input type="checkbox"/> NTX w/o mercury										W									
Electrical connection																			
<input type="checkbox"/> 6-Pin connection																6 P			
<input type="checkbox"/> 8-Pin connection																8 P			
Special design																			
<input type="checkbox"/> No special design																	0 0 0		
<input type="checkbox"/> Special design																		x x x	

* Only available with M18 thread connection.
 ** As a standard, all diaphragms are coated against adhesive and glutinous media. Special coatings are available on request.
 ** For cable exit, please confirm cable length. Unless specified, the standard length will be 3 m.