

Use this form to generate your exact part number. Then telephone (847) 981-0003 or fax (847) 981-9333 for price and delivery.



**Order specification DAI series Mercury  
Pressure Transmitter with V or mA output**

Order specification	DAI																												
<b>Standard configuration</b>																													
<input type="checkbox"/> <b>DAI</b>																													
<b>Total measurement error FSO</b>																													
<input type="checkbox"/> 0.25%			1																										
<input type="checkbox"/> 0.50%			2																										
<b>Output signal</b>																													
<input type="checkbox"/> 4-20 mA (2-wire)			E	2																									
<input type="checkbox"/> 4-20 mA (3-wire)			E	3																									
<input type="checkbox"/> 4-20 mA (4-wire)			E	4																									
<input type="checkbox"/> 0-20 mA (3-wire)			D	3																									
<input type="checkbox"/> 0-20 mA (4-wire)			D	4																									
<input type="checkbox"/> 0-10 V (3-wire)			C	3																									
<input type="checkbox"/> 0-10 V (4-wire)			C	4																									
<b>Thread connection</b>																													
<input type="checkbox"/> 1/2" UNF 2A					1	2	A																						
<input type="checkbox"/> M18 x 1,5 A					1	8	A																						
<input type="checkbox"/> M18 x 1,5 B					1	8	B																						
<b>Pressure range [psi]</b>																													
<input type="checkbox"/> 250		*						P	2	5	Z																		
<input type="checkbox"/> 500		*						P	5	0	Z																		
<input type="checkbox"/> 750		*						P	7	5	Z																		
<input type="checkbox"/> 1500								P	1	5	H																		
<input type="checkbox"/> 3000								P	3	0	H																		
<input type="checkbox"/> 5000								P	5	0	H																		
<input type="checkbox"/> 6000								P	6	0	H																		
<input type="checkbox"/> 7500								P	7	5	H																		
<input type="checkbox"/> 9000								P	9	0	H																		
<input type="checkbox"/> 10000								P	1	0	T																		
<input type="checkbox"/> 12000								P	1	2	T																		
<input type="checkbox"/> 15000								P	1	5	T																		
<input type="checkbox"/> 20000								P	2	0	T																		
<input type="checkbox"/> 30000								P	3	0	T																		
<b>Shaft length (rigid)</b>																													
<input type="checkbox"/> 152 mm, 6" (standard)																				S	0								
<input type="checkbox"/> 203 mm, 8,0"																					S	1							
<input type="checkbox"/> 254 mm, 10,0"																						S	2						
<input type="checkbox"/> 318 mm, 12,5"																							S	3					
<input type="checkbox"/> 356 mm, 14,0"																							S	4					
<input type="checkbox"/> 457 mm, 18,0"																							S	5					
<input type="checkbox"/> Special shaft length																							S	9					
<b>Length of flexible capillary</b>																													
<input type="checkbox"/> <b>No flexible capillary</b>																							F	0					
<input type="checkbox"/> 457 mm, 18" (standard)																								F	5				
<input type="checkbox"/> 610 mm, 24"																									F	6			
<input type="checkbox"/> 760 mm, 30"																									F	8			
<input type="checkbox"/> Special length																									F	9			
<b>Diaphragm</b>																													
<input type="checkbox"/> 17-4 PH		**																						R					
<input type="checkbox"/> Alloy C4		**																							H				
<input type="checkbox"/> Alloy 718		**																							I				
<input type="checkbox"/> Special diaphragm																									S				
<b>Sensor medium</b>																													
<input type="checkbox"/> Mercury "M" Group																									M				
<b>Electrical connection</b>																													
<input type="checkbox"/> 6-pole connection (standard)																									6	P			
<input type="checkbox"/> 6-pole connection (type 98)																										9	8		
<input type="checkbox"/> 8-pin connection																										8	P		
<b>Special design</b>																													
<input type="checkbox"/> <b>No special design</b>																										0	0	0	
<input type="checkbox"/> Special design																											x	x	x

\* Only available with M18 thread connection.  
 \*\* As a standard, all diaphragms are coated against adhesive and glutinous media. Special coatings are available on request.  
 \*\*\* For cable exit, please confirm cable length. Unless specified, the standard length will be 3 m.