



Order specification **DAIX series - NTX non-mercury**
Explosion-Proof Pressure Transducer with **4-20 mA** output

Order specification	DAIX																			
Standard configuration																				
<input type="checkbox"/> DAIX																				
Total measurement error FSO																				
<input type="checkbox"/> 0.25%																				
<input type="checkbox"/> 0.50%																				
Output signal																				
<input type="checkbox"/> 4-20 mA (2-wire)																				
Thread connection																				
<input type="checkbox"/> 1/2" UNF 2A																				
<input type="checkbox"/> M18 x 1,5 A																				
<input type="checkbox"/> M18 x 1,5 B																				
Pressure range [bar]																				
<input type="checkbox"/> 250																				
<input type="checkbox"/> 500																				
<input type="checkbox"/> 750																				
<input type="checkbox"/> 1500																				
<input type="checkbox"/> 3000																				
<input type="checkbox"/> 5000																				
<input type="checkbox"/> 6000																				
<input type="checkbox"/> 7500																				
<input type="checkbox"/> 9000																				
<input type="checkbox"/> 10000																				
<input type="checkbox"/> 12000																				
<input type="checkbox"/> 15000																				
<input type="checkbox"/> 20000																				
<input type="checkbox"/> 30000																				
Shaft length (rigid)																				
<input type="checkbox"/> 152 mm, 6" (standard)																				
<input type="checkbox"/> 203 mm, 8,0"																				
<input type="checkbox"/> 254 mm, 10,0"																				
<input type="checkbox"/> 318 mm, 12,5"																				
<input type="checkbox"/> 356 mm, 14,0"																				
<input type="checkbox"/> 457 mm, 18,0"																				
<input type="checkbox"/> Special shaft length																				
Length of flexible capillary																				
<input type="checkbox"/> No flexible capillary																				
<input type="checkbox"/> 457 mm, 18" (standard)																				
<input type="checkbox"/> 610 mm, 24"																				
<input type="checkbox"/> 760 mm, 30"																				
<input type="checkbox"/> Special length																				
Diaphragm																				
<input type="checkbox"/> 17-4 PH **																				
<input type="checkbox"/> Alloy C4 **																				
<input type="checkbox"/> Alloy 718 **																				
<input type="checkbox"/> Special diaphragm																				
Sensor medium																				
<input type="checkbox"/> Non-mercury NTX																				
Electrical connection																				
<input type="checkbox"/> 6-pole connection (standard)																				
<input type="checkbox"/> 6-pole connection (type 98)																				
<input type="checkbox"/> Cable exit stainless steel, 3m ***																				
Special design																				
<input type="checkbox"/> No special design																				
<input type="checkbox"/> Special design																				

* Only available with M18 thread connection.

** As a standard, all diaphragms are coated against adhesive and glutinous media. Special coatings are available on request.

*** For cable exit, please confirm cable length. Unless specified, the standard length will be 3 m.