Use this form to generate your part number. Then telephone (847) 981-0003 or fax (847) 981-9333 for price and del

Price list + order specification RD series - Gneuss Inc.
Extrusion PRD (pressure relief device) Rupture Discs

Order specification	RD	-			-			-				-		-			-			-			-			
Standard configuration																										
	RD																									
Burst Tolerance																										
0.10%			**2**																							
Mechanical Configuration																										
Type: Hexagon End				**H E**																						
Thread connection																										
1/2" UNF 2A					**1 2 A**																					
M18 x 1,5 A					1 8 A																					
M18 x 1,5 B					1 8 B																					
Burst Rating psi																										
250	*							P 2 5 Z																		
500	*							P 5 0 Z																		
750	*							P 7 5 Z																		
1500								**P 1 5 H**																		
3000								**P 3 0 H**																		
5000								**P 5 0 H**																		
6000								**P 6 0 H**																		
7500								**P 7 5 H**																		
9000								**P 9 0 H**																		
10000								**P 1 0 T**																		
12000								**P 1 2 T**																		
15000								**P 1 5 T**																		
Shaft length (rigid)																										
152 mm, 6" (standard)									**S 0**																	
203 mm, 8,0"									S 1																	
254 mm, 10,0"									S 2																	
318 mm, 12,5"									S 3																	
356 mm, 14,0"									S 4																	
457 mm, 18,0"									S 5																	
Special shaft length									S 9																	
Temperature Range																										
max temp 500 degrees F											**F 0**															
max temp 800 degrees F											F 5															
											F 6															
											F 8															
other											F 9															
Stem Assembly Material																										
300 S/S	**											**R**														
Alloy C4	**											H														
Alloy 718	**											I														
Special diaphragm												S														
Disk Material																										
Inconel												**I**														
other												**O**														
Special design																										
Standard design												**S**														
	***																									
Special design																										
no special design																									**0 0 0**	
Special design																									x x x	

* Only available with M18 thread connection.

** As a standard, all diaphragms are coated against adhesive and glutinous media.
Special coatings are available on request.

*** For cable exit, please confirm cable length. Unless specified, the standard length will be 3 m.